

GSXR 150

THE ROAD CONQUEROR



GSX-R 150

BIKE FEATURES



4-STROKE, DOHC,
4-VALVE, 6- SPEED



Vertically Stacked LED
Headlights



Tail Light and LED License
Plate Light



Tubeless Tires with
10-spoke Cast Wheels



High-performance
Exhaust System



Key-less Ignition
System



Suzuki Easy Start
System



Decent Steering Angle



Metallic Titan Blue (YSF)



Stronger Red / Titan Black [GTA]

SPECIFICATIONS

ENGINE	Type	Twincam 4 Valve, DOHC, 4 Stroke
	Cooling System	Liquid Cooled
	Bore x Stroke	62.0 x 48.8 mm
	Displacement	147 cc
	Ignition System	Electronic Transistorized
	Compression Ratio	11.5 : 1
	Carburetion	Fuel Injection
	Starter System	Electric
	Lubrication System	SJCS (Suzuki Jet Cooling System)
	TRANSMISSION	Clutch System
Transmission		6 Speed Constant Mesh
CHASSIS	Suspension Front	Telescopic, Coil Spring, Oil Damped
	Suspension Rear	Mono Shock with Swingarm (Link Type)
	Brake Front	Disc Brake
	Brake Rear	Disc Brake
	Tire Size Front	90/80-17M/C 46P (Tubeless)
	Tire Size Rear	130/70-17M/C 62P (Tubeless)
	Wheel Type	Cast Wheel
	Fuel Tank Capacity	11.0 Liter
DIMENSIONS	Width x Length x Height	700 x 2,000 x 1,070 mm
	Wheelbase	1,300 mm
	Ground Clearance	160 mm
	Seat Height	785 mm
	Caster/Trail	26°/ 93 mm
	Full Weight	135 kg



SUZUKI MALAYSIA SDN. BHD. 202001012115 (1368435-X)

(Exclusive & Sole Importer / Assembler / Distributor for Suzuki Motorcycle, Scooter, ATV, Spare Parts & Accessories)

No.12 & 14, Jalan Jurunilai U1/20, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan.

Tel: 603-5566 5688 Fax: 603-5566 5699

[f suzukimalaysia](https://www.facebook.com/suzukimalaysia) [ig suzukimalaysiasb](https://www.instagram.com/suzukimalaysiasb) [tw suzukimalaysia1](https://www.twitter.com/suzukimalaysia1) www.suzuki.com.my

* Specifications are subject to change without prior notice
** Pictures displayed are for illustration purposes only.
Actual product may vary.

